

# Adexin<sup>®</sup> ZE

## Cement film remover

### Description

ADEXIN ZE is a liquid cleaner for removing cement and lime films, efflorescence, (not sulphate efflorescence), cement and mortar splashes.

Main features:

- High cleaning performance
- Can be diluted with water

### Product data

Base	organic acids, water
Colour	transparent
Consistency	liquid
Density	app. 1.3 kg/dm <sup>3</sup>
Application	brush

### Range of application

ADEXIN ZE is suitable for cleaning concrete, exposed aggregate concrete and clinker surfaces, roughening smooth concrete surfaces and for better adhesion of subsequent paint and coatings.

It is a proven agent for cleaning open-air pools (painted or tiled) and cement mixers. ADEXIN ZE does not attack acid-resistant paints with a plastic base or varnishes, provided the film is non-porous. Other wise it will color the surface or loosen the paint or the varnish by penetrating underneath.

Whenever concrete contains iron and mineral aggregates, ADEXIN ZE will form brown discolorations on its surface. Parts which are not resistant to acids (pipes, window-sills, fittings, gutters), have to be protected from ADEXIN ZE before its application.

The existence of several substrates makes it difficult to estimate the efficiency of ADEXIN ZE. Carry out a test prior to application.

### Working instructions

Thoroughly wet the surface to be treated. ADEXIN ZE is diluted 1 : 1 to 1 : 5 with

clean water, depending on the nature and grade of the dirt. Use only plastic containers for diluting.

Apply the solution with a brush in one or several operations, depending on the dirt. Rubbing increases the effect.

**Then rinse well with water.**

When treating machine parts with ADEXIN ZE, allow to dry thoroughly then spray the release agent RELAX Multi.

### Precautions

ADEXIN ZE is caustic and irritating.

### Delivery and storage

ADEXIN ZE is supplied in 1 litre and 10 litres tins (net weights).

Can be stored cool in its original sealed packaging for at least 12 months.

### Notes

The correct and hence successful application of our products is not within our control. A guarantee can therefore only be accepted for the quality of our products within the framework of our sale and supply conditions but not for their successful use.

Observe the safety precautions for protection of health and prevention of accidents given in the safety data sheet and on the label of the packaging.

This data sheet supersedes all earlier technical data on this product. Information supplied by our employees and/or distributors going beyond the information contained in this data sheet, must be confirmed in writing.

We reserve the right to make changes representing technical progress.